



## Kawasaki ZX-9R Ninja - Installation Instructions

Thank you for selecting and purchasing a TiForce exhaust system for your Kawasaki ZX-9R. TiForce is the world's finest titanium exhaust system available today. Please install your new system as explained in the following pages, and in accordance with given precautions. Instructions are also available in Adobe Acrobat PDF format on the TiForce website ([www.TiForce.com](http://www.TiForce.com)).

### Before Installation:

- Verify that all parts and accessories have been included (see list below).
- Coat all exhaust pipe mating joints with anti-seize compound / lubricant (Finish Line Ti-Prep packet included).
- Read and review these instructions, cautions, diagrams and images prior to starting any work.

- 
1. Remove the lower fairing. Remove the lower radiator mounting bolts, loosen the upper bolts and pivot the radiator forward to provide access to the exhaust nuts (flange nuts). Remove the oil cooler mounting bolts and pivot the oil cooler forward to provide access.
  2. Remove the existing exhaust system and save the flange nuts for reuse. Save the stock exhaust can mounting bolt and nut for reuse as well.
  3. Inspect the exhaust gaskets. Replace if necessary.
  4. Assemble the head pipes 1 (blue), 2 (red), 3 (yellow), and 4 (green) by matching the joints of the same color to the pair of front Y-pipes. Do not install the exhaust springs at this time.
  5. **2000 through 2002 models ONLY!!!** Place a billet aluminum exhaust port centering flange Z on each TiForce headpipe – see figure 3 for details.
  6. Attach the assembled head pipe sections to the exhaust ports, but do not tighten the flange nuts fully, allowing for some adjustment in the remaining steps. Reuse the flange nuts saved from step 2 above. Make sure the ends of the headpipes fit flush and snug in the ports and centering flanges Z before tightening (**'00-'02 ONLY**).
  7. Install the S-Bend to the front section of the headpipes and two Y-pipes.
  8. Go back and retighten the head pipe flange nuts per factory specifications – make sure the headpipes and flanges Z are centered in each port (**'00-'02 ONLY!!!**).
  9. Slide the TiForce end can into place.
  10. Loosely attach the two rubber bands, stainless steel bands K, and stay / hanger G to the end can using the supplied 6mm hardware H. See figure 1.
  11. Place the bands approximately **108mm** from the edge of the end can. See figure 2.
  12. Using the stock provided mounting point on the passenger footpeg, and using the stock mounting bolt, mount the end can loosely, allowing for some adjustment. Insert the stock mounting bolt through the stay / hanger G.
  13. Attach the supplied springs to all the joints, starting from the headpipes and working back to the end can.
  14. Make sure the exhaust system is free and clear, if necessary jiggle the system to adjust for proper clearance.
  15. Carefully align the two stainless bands K so that they are parallel to each other, and spaced properly on the can (refer to step 11 / figure 2), then tighten the 6mm hardware H and the stock mounting bolt hardware. Make sure that the rubber pads fully cover the band(s). **USE CAUTION WHEN TIGHTENING THE 6MM HARDWARE AND THE TWO BANDS SO AS NOT TO CRUSH OR DISTORT THE SLEEVE OF THE CAN.**
  16. Using some brake and contact cleaner on a clean rag, carefully wipe down the entire exhaust system to remove any residual oils, anti seize, fingerprints and dirt prior to starting the motor. **FAILURE TO CLEAN THE TUBING AND CAN MAY RESULT IN PERMANENT STAINING OF THE SYSTEM WHEN HEATED.**
  17. Go back and reinstall the radiator and oil cooler as per factory specifications. Verify fluid levels as needed.
  18. Check that all hardware is properly tightened, then start the motor and check for exhaust leaks.
  19. Reinstall the fairing and tighten any fasteners per factory specification.

---

### General Cautions For Exhaust System Installations:

- **CAUTION** - For your safety, carefully read these instructions and those above, and fully familiarize yourself with the content before beginning installation and use. Keep these instructions in a safe place for future reference. Install the exhaust system as explained in these instructions.
- **DANGER** – when the motor is running, and shortly after it has been turned off, the motorcycle, the exhaust system and end-can will be hot. Severe burns, bodily injury and even death may result.
- **DANGER** - Keep gasoline and other flammable materials away from the exhaust system at all times. Exposure of gasoline and to heat can lead to fire.



- **CAUTION** - Stop the motorcycle should the exhaust system come in contact with people or animals. Never touch the exhaust system when hot. Direct contact with the system can cause burns.
- **DANGER** - Allow the motor to cool before installing or removing the exhaust system. Working with a hot motor can lead to burns.
- **CAUTION** - Stand the motorcycle on a flat and level surface and ensure that the motorcycle is stable before installing the exhaust system. Bodily injury and / or death could result to you or others if the motorcycle falls over. Damage may also result to the motorcycle or nearby property or equipment.
- **DANGER** - Start and run the motorcycle in a well-ventilated area. With prolonged exposure to exhaust gas you run the risk of severe oxygen deficiencies, bodily injury or death may result.
- **CAUTION** - Install the muffler only on the specified model of motorcycle. Improper installation will lead to loss of performance and or damage to the motorcycle.
- **CAUTION** - Do not disassemble, modify or remodel this exhaust system.

---

TiForce high performance exhaust systems are distributed exclusively by Orient Express Powersports. Please have your dealer contact Orient Express for technical assistance, information, and parts if needed.

TiForce / Orient Express  
81 Hanse Ave  
Freeport, NY 11520



800.645.6521  
516.546.5232 tel  
516.546.5247 fax


[www.orientexpress.com](http://www.orientexpress.com)  
[www.tiforce.com](http://www.tiforce.com)  
[sales@tiforce.com](mailto:sales@tiforce.com)



**PARTS LIST (Kawasaki ZX-9R)**

- Exhaust head pipes - #'s 1,2,3,4 - 1 each / 4 total
- Exhaust Y-pipes - 2x
- Exhaust S-bend pipe - 1x
- End can - 1x
- End can stay / hanger G - 1x
- Stainless steel bands K - 2x
- Rubber pads - 2x
- Exhaust springs - 8x
- M6 x 20mm allen bolt H - 2x
- M6 nut - 2x
- M6 washer - 4x
- Finish Line TiPrep Anti-Seize - 1 packet
- Mouthpiece rings Z ('00-'02 ONLY!!!) - 4x





**For Kawasaki ZX-9R '00-'02 model years ONLY!!!**